

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-2317957-0
Report Reference □□E479166-20230506□□
Date 15-May-2023

Issued to: Guangdong Done Power Technology Co., Ltd.
No.3-1&3-2, Kanglong 3rd Road
Henglan Town Zhongshan, Guangdong 528478
China

**This is to certify that
representative samples of**

FKSZ8 - Light-emitting-diode Drivers Certified for Canada -
Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the
component requirements in the Standard(s) indicated on
this Certificate. UL Recognized components are incomplete
in certain constructional features or restricted in
performance capabilities and are intended for installation in
complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: CSA C22.2 No. 250.13, Edition 5, Issue Date 2022-05

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.


Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-2317957-0
Report Reference □□E479166-20230506□□
Date 15-May-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
DL-320U-V56*-MUG, * - Can be "P" or "X". "P" = 0-10V/PWM/Resistor Dimming Function. "X" = 0-10V/PWM/Resistor Dimming Function and AUX output: CV, 12VDC, 0.3A.	LED Drivers
DL-320W-V428*-MXG, * - Can be "X", "T" or "J". "X" = 0-10V/PWM/Resistor Dimming via cord and AUX output: CV, 12VDC, 0.3A. "T" = 0-10V/PWM/Resistor and NTC Dimming via cord and AUX output: CV, 12VDC, 0.3A. "J" = 0-10V/PWM/Resistor Dimming via RJ12 connector, Potentiometer and AUX output: CV, 12VDC, 0.3A.	LED Drivers
DL-500W-V428*-MXG, * - Can be "X", "T" or "J". "X" = 0-10V/PWM/Resistor Dimming via cord and AUX output: CV, 12VDC, 0.3A. "T" = 0-10V/PWM/Resistor and NTC Dimming via cord and AUX output: CV, 12VDC, 0.3A. "J" = 0-10V/PWM/Resistor Dimming via RJ12 connector, Potentiometer and AUX output: CV, 12VDC, 0.3A.	LED Drivers
DL-600W-V428*-MXG, * - Can be "X", "T" or "J". "X" = 0-10V/PWM/Resistor Dimming via cord and AUX output: CV, 12VDC, 0.3A. "T" = 0-10V/PWM/Resistor and NTC Dimming via cord and AUX output: CV, 12VDC, 0.3A. "J" = 0-10V/PWM/Resistor Dimming via RJ12 connector, Potentiometer and AUX output: CV, 12VDC, 0.3A.	LED Drivers
DL-720W-V428*-MXG, * - Can be "X", "T" or "J". "X" = 0-10V/PWM/Resistor Dimming via cord and AUX output: CV, 12VDC, 0.3A. "T" = 0-10V/PWM/Resistor and NTC Dimming via cord and AUX output: CV, 12VDC, 0.3A. "J" = 0-10V/PWM/Resistor Dimming via RJ12 connector, Potentiometer and AUX output: CV, 12VDC, 0.3A.	LED Drivers
DL-960W-V260*-PLS, * - Can be "X", "T" or "J". "X" = 0-	LED Drivers

Deborah Jennings-Conner
Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-2317957-0
Report Reference ☐E479166-20230506☐
Date 15-May-2023

10V/PWM/Resistor Dimming via cord and AUX output: CV, 12VDC, 0.3A. "T" = 0-10V/PWM/Resistor and NTC Dimming via cord and AUX output: CV, 12VDC, 0.3A. "J" = 0-10V/PWM/Resistor Dimming via RJ12 connector, Potentiometer and AUX output: CV, 12VDC, 0.3A.	
---	--

Deborah Jennings-Conner

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2320618-0
Report Reference □□E479166-20230506□□
Date 15-May-2023

Issued to: Guangdong Done Power Technology Co., Ltd.
No.3-1&3-2, Kanglong 3rd Road
Henglan Town Zhongshan, Guangdong 528478
China

**This is to certify that
representative samples of**

FKSZ2 - Light-emitting-diode Drivers - Component
See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 8750, Edition 2, Issue Date 2015-09-15, Revision Date 2022-12-07

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.


Deborah Jennings-Conner, VP Regulatory Services
UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2320618-0
Report Reference □□E479166-20230506□□
Date 15-May-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
DL-320U-V56*-MUG, * - Can be "P" or "X". "P" = 0-10V/PWM/Resistor Dimming Function. "X" = 0-10V/PWM/Resistor Dimming Function and AUX output: CV, 12VDC, 0.3A.	LED Drivers
DL-320W-V428*-MXG, * - Can be "X", "T" or "J". "X" = 0-10V/PWM/Resistor Dimming via cord and AUX output: CV, 12VDC, 0.3A. "T" = 0-10V/PWM/Resistor and NTC Dimming via cord and AUX output: CV, 12VDC, 0.3A. "J" = 0-10V/PWM/Resistor Dimming via RJ12 connector, Potentiometer and AUX output: CV, 12VDC, 0.3A.	LED Drivers
DL-500W-V428*-MXG, * - Can be "X", "T" or "J". "X" = 0-10V/PWM/Resistor Dimming via cord and AUX output: CV, 12VDC, 0.3A. "T" = 0-10V/PWM/Resistor and NTC Dimming via cord and AUX output: CV, 12VDC, 0.3A. "J" = 0-10V/PWM/Resistor Dimming via RJ12 connector, Potentiometer and AUX output: CV, 12VDC, 0.3A.	LED Drivers
DL-600W-V428*-MXG, * - Can be "X", "T" or "J". "X" = 0-10V/PWM/Resistor Dimming via cord and AUX output: CV, 12VDC, 0.3A. "T" = 0-10V/PWM/Resistor and NTC Dimming via cord and AUX output: CV, 12VDC, 0.3A. "J" = 0-10V/PWM/Resistor Dimming via RJ12 connector, Potentiometer and AUX output: CV, 12VDC, 0.3A.	LED Drivers
DL-720W-V428*-MXG, * - Can be "X", "T" or "J". "X" = 0-10V/PWM/Resistor Dimming via cord and AUX output: CV, 12VDC, 0.3A. "T" = 0-10V/PWM/Resistor and NTC Dimming via cord and AUX output: CV, 12VDC, 0.3A. "J" = 0-10V/PWM/Resistor Dimming via RJ12 connector, Potentiometer and AUX output: CV, 12VDC, 0.3A.	LED Drivers
DL-960W-V260*-PLS, * - Can be "X", "T" or "J". "X" = 0-	LED Drivers

Deborah Jennings-Conner
Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2320618-0
Report Reference ☐E479166-20230506☐
Date 15-May-2023

10V/PWM/Resistor Dimming via cord and AUX output: CV, 12VDC, 0.3A. "T" = 0-10V/PWM/Resistor and NTC Dimming via cord and AUX output: CV, 12VDC, 0.3A. "J" = 0-10V/PWM/Resistor Dimming via RJ12 connector, Potentiometer and AUX output: CV, 12VDC, 0.3A.	
---	--

Deborah Jennings-Conner
Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

