

# IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

## CB TEST CERTIFICATE

Product

LED Driver

Name and address of the applicant

Guangdong Done Power Technology Co.,Ltd.  
No.3-1&3-2, Kanglong 3rd Road, Henglan Town, Zhongshan,  
528478 Guangdong, P.R. China

Name and address of the manufacturer

Guangdong Done Power Technology Co.,Ltd.  
No.3-1&3-2, Kanglong 3rd Road, Henglan Town, Zhongshan,  
528478 Guangdong, P.R. China

Name and address of the factory

Note: When more than one factory, please report on page 2

Guangdong Done Power Technology Co.,Ltd.  
No.3-1&3-2, Kanglong 3rd Road, Henglan Town, Zhongshan,  
528478 Guangdong, P.R. China

Ratings and principal characteristics

Independent constant current LED driver, IP67  
AC Input: 1)100-277V, 50/60Hz, 0.25A;  
2)100-277V, 50/60Hz, 0.32A; 3)100-277V, 50/60Hz, 0.37A;  
4)100-277V, 50/60Hz, 0.46A; 5)100-277V, 50/60Hz, 0.6A;  
6)100-277V, 50/60Hz, 0.72A; 7)100-277V, 50/60Hz, 0.9A  
DC Output: Refer to page 2.

Trademark / Brand (if any)

DONE

Customer's Testing Facility (CTF) Stage used

N/A

Model / Type Ref.

1) DL-40H-260z-PXC, 2) DL-50H-260z-PXC,  
3) DL-60H-260z-PXC, 4) DL-75H-260z-PXC,  
5) DL-100H-260z-PXC, 6) DL-120H-260z-PXC,  
7) DL-150H-260z-PXC  
(z = A or P)

Additional information (if necessary may also be reported on page 2)

See additional page(s) for further Additional information.  
For model differences, refer to the test report.  
Re-issue of JPTUV-162506 dated 05.07.2024,  
due to first modification.

A sample of the product was tested and found to be in conformity with

IEC 61347-2-13:2014+A1  
IEC 61347-1:2015+A1

As shown in the Test Report Ref. No. which forms part of this Certificate

CN24EBJ6 002

This CB Test Certificate is issued by the National Certification Body



TÜV Rheinland Japan Ltd.  
4-25-2 Kita-Yamata, Tsuzuki-ku  
Yokohama 224-0021, Japan  
Mail: info@jpn.tuv.com

Date: 2025-04-25

Signature:

Martin Wang

**Additional information :**

DC Output: 180-260V

- 1) 0.04-0.1A at AC 100-180V  
0.08-0.2A at AC 180V-277V;  
20W Max. at AC 100-180V  
40W Max. at AC 180V-277V
- 2) 0.05-0.125A at AC 100-180V  
0.1-0.25A at AC 180V-277V;  
25W Max. at AC 100-180V  
50W Max. at AC 180V-277V
- 3) 0.058-0.15A at AC 100-180V  
0.115-0.3A at AC 180V-277V;  
30W Max. at AC 100-180V  
60W Max. at AC 180V-277V
- 4) 0.95-0.19A at AC 100-180V  
0.19-0.38A at AC 180V-277V;  
37.5W Max. at AC 100-180V  
75W Max. at AC 180V-277V
- 5) 0.135-0.25A at AC 100-180V  
0.27-0.5A at AC 180V-277V;  
50W Max. at AC 100-180V  
100W Max. at AC 180V-277V
- 6) 0.19-0.3A at AC 100-180V  
0.38-0.6A at AC 180V-277V;  
60W Max. at AC 100-180V  
120W Max. at AC 180V-277V
- 7) 0.19-0.375A at AC 100-180V  
0.38-0.75A at AC 180V-277V;  
75W Max. at AC 100-180V  
150W Max. at AC 180V-277V



Date: 2025-04-25

Signature:

as on page 1