



APPROVALS®

Certificate of Suitability

Certificate No.: SAA220453

Certificate Holder: Guangdong Done Power Technology Co., Ltd.
No. 3-1&3-2, Kanglong 3rd Road,
Henglan Town, Zhongshan,
528478 Guangdong
P.R. China

Regulatory Definition: Non-Prescribed

Product Description: LED Driver (Built-in, Non-SELV, Constant current, Dimmable)

Standard/s: AS/NZS 61347.2.13:2018
AS/NZS 61347.1:2016 Inc A1

Condition/s: Must comply with standard requirements of
end-product when installed.
For use with LED lighting only.

Approval Marks: RCM (In accordance with AS/NZS 4417 and EESS requirements)
and
SAA220453

Initial Issue Date: 26 July 2022

Expiry Date: 26 July 2027

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 26-07-22 220453
Page 1 of 2



APPROVALS®

Certificate of Suitability

Model	Trade Name	Rating / Marking
DL-150W- V260X-SPF	DONE	Input: 120-277V~ 50/60Hz 1.5A Output: 180-260Vdc 0.35-0.75A, No load output:300Vdc, Prated: Max 150W, ta:55°C, tc:90°C, IP65, Class I
DL-150W- V260S-SPF	DONE	Input: 120-277V~ 50/60Hz 1.5A Output: 180-260Vdc 0.35-0.75A No load output:300Vdc, Prated: Max 150W, ta:55°C, tc:90°C, IP65, Class I
DL-150W- V260A-SPF	DONE	Input: 120-277V~ 50/60Hz 1.5A Output: 180-260Vdc 0.35-0.75A No load output:300Vdc, Prated: Max 150W, ta:55°C, tc:90°C, IP65, Class I
DL-120W- V260X-SPF	DONE	Input: 120-277V~ 50/60Hz 1.2A Output: 180-260Vdc 0.25-0.6A No load output:300Vdc, Prated: Max120W, ta:55°C, tc:90°C, IP65, Class I
DL-120W- V260S-SPF	DONE	Input: 120-277V~ 50/60Hz 1.2A Output: 180-260Vdc 0.25-0.6A No load output:300Vdc, Prated: Max120W, ta:55°C, tc:90°C, IP65, Class I
DL-120W- V260A-SPF	DONE	Input: 120-277V~ 50/60Hz 1.2A Output: 180-260Vdc 0.25-0.6A No load output:300Vdc, Prated: Max120W, ta:55°C, tc:90°C, IP65, Class I

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 26-07-22 220453
Page 2 of 2